



金属电缆软管

Meleon A



材质	镀锌钢
防护等级	IP 40
环境温度	-100 °C – 300 °C (-148°F – 572°F)



尺寸 DN	d mm	D mm	 mm	订货号
7	7,5	10,5	25	1.560.0760.00
9	9	12	30	1.560.0960.00
11	11	14	30	1.560.1160.00
14	14	17	40	1.560.1460.00
16	16	19	45	1.560.1660.00
21	21	24	55	1.560.2160.00
26	26	30	55	1.560.2660.00
37	37	41	80	1.560.3760.00
40	40	44	80	1.560.4060.00
51	51	55	90	1.560.5160.00


Meleon B

RoHS

材质 镀锌钢,PVC 覆层

防护等级 IP 65

环境温度 -15 °C – 70 °C (5°F – 158°F)



尺寸 DN	d mm	D mm	R mm	订货号
7	7,5	11,5	25	1.561.0761.00
9	9	13	30	1.561.0961.00
11	11	15	30	1.561.1161.00
14	14	18	40	1.561.1461.00
16	16	20	45	1.561.1661.00
21	21	25	55	1.561.2161.00
26	26	31	55	1.561.2661.00
37	37	42	80	1.561.3761.00
40	40	45	80	1.561.4061.00
51	51	56	90	1.561.5161.00


金属配件


MeleonFit



材质	黄铜镀镍
防护等级	IP 54
环境温度	-20 °C – 80 °C (-4 °F – 176 °F)

RoHS





尺寸	d mm	GL mm	H mm	 mm	适配	订货号
M 12	6	8	24	15	7	1.570.1260.50
M 16	7	8	24	20	9	1.570.1660.51
M 16	9	10	26	20	11	1.570.1660.50
M 20	12	10	26	22	14	1.570.2060.51
M 20	14	10	26	22	16	1.570.2060.50
M 25	18	10	27	28	21	1.570.2560.50
M 32	23	12	31	35	26	1.570.3260.50
M 40	33,5	14	36	45	37	1.570.4060.50
M 50	37	14	36	55	40	1.570.5060.50
M 63	46	14	36	65	51	1.570.6360.50
PG 7	6	8	24	15	7	1.570.0760.14
PG 9	7	8	24	17	9	1.570.0960.14
PG 11	9	10	26	20	11	1.570.1160.14
PG 13,5	12	10	26	22	14	1.570.1360.14
PG 16	14	10	26	24	16	1.570.1660.14
PG 21	18	10	27	30	21	1.570.2160.14
PG 29	23	12	31	40	26	1.570.2960.14
PG 36	33,5	14	36	50	37	1.570.3660.14
PG 42	37	14	36	60	40	1.570.4260.14
PG 48	46	14	36	65	51	1.570.4860.14

MeleonFit S

RoHS

材质	黄铜镀镍
防护等级	IP 54
环境温度	-20 °C – 80 °C (-4 °F – 176 °F)



尺寸	d mm	GL mm	H mm	 mm	适配	订货号
M 12	6	8	27	15	7	1.571.1260.50
M 16	7	8	27	20	9	1.571.1660.51
M 16	9	10	29	20	11	1.571.1660.50
M 20	12	10	29	22	14	1.571.2060.51
M 20	14	10	29	22	16	1.571.2060.50
M 25	18	10	31	28	21	1.571.2560.50
M 32	23	12	35	35	26	1.571.3260.50
M 40	33,5	14	41	45	37	1.571.4060.50
M 50	37	14	41	55	40	1.571.5060.50
M 63	46	14	41	65	51	1.571.6360.50
PG 7	6	8	27	15	7	1.571.0760.14
PG 9	7	8	27	17	9	1.571.0960.14
PG 11	9	10	29	20	11	1.571.1160.14
PG 13,5	12	10	29	22	14	1.571.1360.14
PG 16	14	10	29	24	16	1.571.1660.14
PG 21	18	10	31	30	21	1.571.2160.14
PG 29	23	12	35	40	26	1.571.2960.14
PG 36	33,5	14	41	50	37	1.571.3660.14
PG 42	37	14	41	60	40	1.571.4260.14
PG 48	46	14	41	65	51	1.571.4860.14